

C2EFL05TT

ELECTRIC GRIDDLE PLATE SMOOTH TOP - SOLUTION LINE



PRODUCT DESCRIPTION

Stainless steel frame. Athermic thermoset plastic knobs with useful screen printed edges.

Heating obtained through **tubular heating elements with stainless steel sheath** placed in direct contact with the cooking plate. Temperature regulation through a thermostat. Working temperatures between 90°C and 300°C. Safety thermostat with manual reset against equipment malfunctioning.

Single large, thick cooking plate with smooth finish that allows excellent heat transmission. **Welded splash guard**. The cooking plate is installed on the worktop with a **slight inclination** to allow grease to flow towards the drain.

Smooth cooking plate.

AISI 304 stainless steel worktop with rounded corners for easy cleaning. Stainless steel front, side and back panels.

Large hole on the cooking surface for draining fats into a large capacity container placed under the cooking surface itself. **Standard equipped** with a grease collection container.

A Teflon plug, suitable to plug the drain in case of any cooking with a film of oil, available **on demand**.

Laser-cut work top finishing for "head-to-head" matching and binding fastening.

Accessories available **on demand**.



TECHNICAL SPECIFICATIONS

Width: 400 mm

Depth: 700 mm

Height: 265 mm

Weight: 68 kg

Volume: 27.00 m³

Electrical power: 4.10 kW

Gas power: 0.21 kW



C2EFL05TT

FRY TOP ELETTRICO DA BANCO PIASTRA LISCIA IN ACCIAIO DOLCE CON PARASPRUZZI

**PLAQUE A SNACKER ELECTRIQUE A POSER LISSE EN ACIER DOUX AVEC PARE-JETS
ELECTRIC GRIDDLE PLATE SMOOTH TABLE TOP MADE OF MILD STEEL WITH SPLASH-GUARDS**


ELEKTROGRIDDLEPLATTE TISCHGERÄT GLATTE BRATFLÄCHE AUS WEICHEM STAHL MIT SPRITZSCHUTZ

FRY TOP ELECTRICO DE BANCO PLANCHA LISA EN ACIERO DULCE CON CHAPA ANTISALPICADURAS

ГЛАДКАЯ ЭЛЕКТРИЧЕСКАЯ ЖАРОЧНАЯ ПОВЕРХНОСТЬ НАСТОЛЬНАЯ СТАЛЬНАЯ ПЛИТА С ЗАЩИТНЫМИ ЭКРАНАМИ

DATI TECNICI / CARACTERISTIQUES TECHNIQUES / TECHNICAL SPECIFICATIONS / TECHNISCHE DATEN / CARACTERISTICAS TECNICAS / ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ

Dimensioni / Dimensions / Dimensions / Maße / Medidas / Размеры	[mm]	400x700x255
Potenza elettrica / Puissance électrique / Electric Power / Elektro-Leistung / электр. (E)	[Kw] - [кВт]	4,1
(F)	[V]	400/3N
(G)	[Hz] - [Гц]	50/60
Cavo (non fornito in dotazione) / Cable (non fourni) / Cable (not supplied) / Kabel (nicht mitgeliefert) / Cable / Кабель	H07 RN-F [mm ²]	5 x 1,5
Voltaggi diversi e versioni navali disponibili su richiesta / Différentes tensions et versions maritimes disponibles sur demande / Different voltages and marine versions available on request / Verschiedene Spannungen und Schiffsausführungen auf Anfrage erhältlich / Различные напряжения и варианты исполнения корабля - по запросу		
Piastra liscia in acciaio dolce con paraspruzzi Plaque lisse en acier doux avec pare-jets Smooth plate of mild steel with splash-guards Glatte Bratfläche aus weichem Stahl mit Spritzschutz Plancha lisa en acero dulce con chapa antisalpicaduras Гладкая конфорка Стальная плита с защитными экранами		X



E= elettrico \ électrique \ electric\ Elektrisch \ eléctrico \ электрич