

K6GCUS10TT

TOP GAS RANGE 4 BURNERS



PRODUCT DESCRIPTION

Stainless steel frame. Athermic thermoset plastic knobs.

Heating by **cast-iron, sealed, stabilised flame and superimposed double crown burners of 6.5 kW maximum.**

Each burner provided with a **safety gas cock**, which enables the output to be regulated from maximum to minimum. Safety ensured by a thermocouple kept active by the burner flame.

Surface grids made of steel covered by material.

Surface grids placed on moulded surfaces with rounded edges and water-tight burners for easy cleaning.

Laser-cut work top finishing for "head-to-head" matching and binding fastening.

Tested with natural gas or LPG, according to the user's needs.

Accessories available **on demand**.



TECHNICAL SPECIFICATIONS

Width: 600 mm
Depth: 600 mm
Height: 295 mm
Weight: 19 kg
Volume: 0.21 m³
Gas power: 26.00 kW



K6GCUS10TT

CUCINA GAS 4 FUOCHI DA BANCO / FOURNEAU À GAZ 4 BRÛLEURS À POSER / TOP GAS RANGE 4 BURNERS TABLE TOP / GASHERD 4 KOCHSTELLEN TISCHGERÄT / COCINAS A GAS 4 QUEMADORES DE BANCO / ГАЗОВАЯ ПЛИТА С 4 КОНФОРКАМИ НАСТОЛЬНАЯ

DATI TECNICI / CARACTERISTIQUES TECHNIQUES / TECHNICAL SPECIFICATIONS / TECHNISCHE DATEN / CARACTERISTICAS TECNICAS / ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ

Dimensioni / Dimensions / Dimensions / Maße / Medidas / Размеры	[мм]	600x600x295
Gas / Gaz / Gas / Gas / Газ (B)	[Kw] - [кВт]	26
Tipo / Type / Type / Typ / Тип (A)		A1
GPL/LPG / Сжиженный нефтяной газ (G30) (D)	[Kg/h] [кг/ч]	1,735 (30 mbar)
Metano / Methane / Natural gas / Erdgas / Метан (G20) (C)	[m3/h] [м3/ч]	2,751
Aria / Air / Luft / Aire / Воздух	[m3/h] [м3/ч]	52
Racc. Gas / Racc. Gaz / Gas fitting / Gasanschluss / Empalme gas / Газовое соединение		UNI-ISO 7/1 R ½
Bruciatore / Bruleur / Burner / Brenner/Quegador / Горелка (F)	[kW] [кВт]	4 x 6,5

A

K6GCUS05TT

6,5 kW

6,5 kW

B

K6GCUS10TT

6,5 kW

6,5 kW

6,5 kW

6,5 kW

G = Gas / Gaz / Gas / Gas / Gas / газ